

Colt XL8

OUTSTANDING OUTDOOR
PERFORMANCE WITH
LUXURIOUS FEATURES

COLT XL8


The **Colt XL8** features a powerful drivetrain and large 33 cm (13") wheels to handle rugged outdoor terrain. Luxury touches like a wraparound delta tiller, low-profile, non-marking tyres and an LED kerb light blend seamlessly to give the Colt XL8 a sleek, sporty style.



Colt XL8

Weight capacity:	28 Stone 8 lbs. (181 kg)
Maximum speed ¹ :	Up to 12.87 km/h (8 mph)
Ground clearance ² :	11.76 cm (4.63") (deck to ground)
Turning radius:	169.54 cm (66.75")
Overall length ² :	134.6 cm (53")
Overall width ² :	64.13 cm (25.25")
Front tyres:	10 cm x 33 cm (4" x 13")
Rear tyres:	10 cm x 33 cm (4" x 13")
Suspension:	Front & rear
Range per charge:	Up to 28.6 km (17.8 miles) with 55 AH batteries Up to 39.6 km (24.6 miles) with 70 AH batteries
Maximum obstacle climbing ability:	5 cm (2")
Total weight without batteries:	97.52 kg (215 lbs.)
Heaviest piece when disassembled:	40.82 kg (90 lbs.) front section
Standard seating:	Type: CRS Deluxe Weight: 21.77 kg (48lbs.) Material: Black Vinyl Dimensions: 46 cm (18") overall width 46 cm (18") effective depth
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Battery requirements ³ :	Two 12-volt, deep cycle Size: 55 AH or 70 AH Weight: 55 AH: 17.16 kg (37.83 lbs.) each; 70 AH: 25 kg (55 lbs.)
Battery charger:	5-amp, off-board

Colours:



Features

- Large 33 cm (13") solid tyres for excellent outdoor performance
- Full lighting package including directional signals and angle-adjustable, LED headlight
- Delta tiller with wraparound handles
- Front basket standard
- Easily accessible tie-down points (for transport of unoccupied scooter)
- Rearview mirror standard

Options

- Forearm crutch holder
- Cane/crutch holder
- Wishbone crutch holder
- Oxygen tank holder
- Rear basket
- Safety flag
- Walker holder
- 70 AH batteries

¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or gel cell type required.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.