

Jazzy[®] **SELECT**

The highly manoeuvrable Jazzy[®] Select delivers the advantages of in-line motor technology for enhanced efficiency, torque, range, and performance. Plus, it's loaded with performance and convenience features, like standard Active-Trac[®] Suspension, that make it as easy to enjoy as it is to use.



Pride[®]
Mobility Products Ltd.
— LIVE YOUR BEST —

SPECIFICATIONS

Weight capacity	136 kg (21 Stone 6 lbs.)
Maximum speed ¹	Up to 6.44 km/h (4 mph)
Ground clearance	4.76 cm (1.875") at midframe
Turning radius ⁴	50.8 cm (20")
Overall length ⁴	90.80 cm (35.75") without front riggings
Overall width ⁴	60.32 cm (23.75")
Drive wheels	Drive: 25.4 cm (10")
Anti-tips	12.7 cm (5") solid, front-mounted
Castors	15.24 cm (6") solid, rear-mounted
Suspension	Active-Trac®
Drivetrain	Two-motor, mid-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	40 amp, PG GC 2 controller
Specialty controls	N/A
Battery charger	Off-board, 5 amp
Battery requirements	(2) 12 volt deep cycle
Battery size (largest)	30 AH
Battery weight ²	11.11 kg (24.5 lbs.) each
Base weight	40.82 kg (90 lbs.)
Standard seat weight	19 kg (42.5 lbs.) (high-back)
Standard seating dimensions	46 cm x 46 cm (18" x 18")
Warranty	Lifetime warranty on frame; 1-year limited warranty on electronics; 18-month warranty on PG Drive control system; 2-year limited warranty on drivetrain

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

1) Speed varies with user weight, terrain type, battery charge, battery condition and tyre pressure.

2) Battery weight may vary based on manufacturer.

3) These are optional (additional) for configuration 1.

4) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%.

FEATURES

- 40 amp, PG GC 2 controller
- Built with ease of service in mind
- Easy side access to batteries
- Toolless front panel access to electronics to minimize service time
- Active-Trac® Suspension

OPTIONS

- Cup holder
- Rear basket
- Oxygen tank holder
- Cane/crutch holder
- Walker holder

COLOUR CHOICES



Red



Blue



PRIDE
PERFORMANCE MOBILITY
— LIVE YOUR BEST® —

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk