# Outstanding **Outdoor Performance** with Luxurious Features



33 cm (13") Pneumatic Tyres



Easy Drive Tiller



**Full Suspension** 



Full Lighting Package

The Pathrider® 130 XL incorporates a blend of power, style and performance to handle rugged outdoor terrain. The powerful drivetrain, 24 Volt, 4-pole motor for increased power, 9.69 cm (3.81") ground clearance and maximum speed of 15 km/h (9.5 mph) combine power and torque to accelerate your active lifestyle. Standard features include feather touch disassembly, wraparound delta tiller, 33 cm (13") pneumatic tyres, front and rear suspension, high-back reclining seat, full lighting package, infinitelyadjustable tiller, front basket and rearview mirror. Available in Red and Silver.

PATHRIDER

**PRIDE® MOBILITY SCOOTERS** LIVE YOUR BEST®

pridemobility.com.au | 🚹 🖸 💟 🐻



130 XI

**4-Wheel Scooter** 

# PATHRIDER 130 XL

## Specifications 4W: S713

| I                                   |   |
|-------------------------------------|---|
| Weight Capacity                     | 159 kg (350 lbs.)   |
| Maximum Speed <sup>1</sup>          | Variable up to 15 km/h (9.5 mph)  |
| Ground Clearance <sup>2</sup>       | 9.69 cm (3.81")   |
| Turning Radius <sup>2</sup>         | 170 cm (67")  |
| Overall Length <sup>2</sup>         | 136 cm (53.54")   |
| Overall Width <sup>2</sup>          | 63.65 cm (25″)  |
| Seat-to-floor Height                | 63 cm - 67 cm (25″ - 26″)   |
| Front Tyres                         | 10 cm x 33 cm (4" x 13") pneumatic  |
| Rear Tyres                          | 10 cm x 33 cm (4" x 13") pneumatic  |
| Range Per Charge <sup>2,4</sup>     | Up to 39.5 km (24.58 miles)   |
| Total Weight<br>Without Batteries   | 65.28 kg (143 lbs.)   |
| Heaviest Piece<br>When Disassembled | 43 kg (94.5 lbs.) front section   |
| Standard Seating                    | Type: High-back, pillow-top<br>Weight: 24.9 kg (55 lbs.)<br>Material: Black Vinyl<br>Dimensions: Width: 49.5 cm (19.5")<br>Depth: 40.6 cm (16") |
| Motor Output                        | 24-volt DC motor, sealed mini-transaxle   |
| Brakes                              | Electronic, regenerative and electromechanical  |
| Battery Requirements <sup>3,5</sup> | (2) 12V deep-cycle<br>Size: (2) 75 AH (Group 24)<br>Weight: 23.9 kg (52.8 lbs.)   |
| Battery Charger                     | Off-board, 8 amp  |
| Colour                              | Mercury Silver Candy Apple Red  |
|                                     |   |

PRIDE<sup>®</sup> MOBILITY SCOOTERS LIVE YOUR BEST<sup>®</sup>

NAME OF TAXABLE PARTY.

### Features

- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and angleadjustable, dual bulb lower LED headlight
- Seat post suspension for a smoother ride
- Easy drive tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard

# Options

- Pride<sup>®</sup> rear bag (includes crutch/ walking stick holder)
- Walker holder (must have Pride<sup>®</sup> rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Sun canopy (must have Pride<sup>®</sup> rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag
- Rearview mirror
- Rear pod
- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
  AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

#### NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.





20-24 Apollo Drive Hallam, Victoria 3803 ACN 088 609 661 ABN 66 088 609 661 (Tel) 03 8770 9600 • (Fax) 03 9703 2720 • www.pridemobility.com.au

AU-PATHRIDER 130XL-SS-12--01-17