MODEL

Jazzy Select 2S-SS ¹	Group 2: Standard (K0822)
Jazzy Select 2S-C ¹	Group 2: Standard (K0823)

Weight Capacity300 lbs.Turning Radius22.5"Overall Width³23.75"Overall Length³32.99"/44" (with footplate)Maximum Speed²Up to 4.3 mphGround Clearance³.75" at motor bracketFront Wheels5" solidDrive Wheels10" solidRear Wheels6" solidDrivetrainTwo motor, mid-wheel drive®Braking SystemRegenerative and electromechanicalSuspension TypeActive-Trac® (ATS)High-back Seat Sizes16" x 16"-18", 18" x 18" x 18"-20", 20" x 18"-20"Seat-to-Floor Range21"-22"Per Charge Range³.5Up to 19.4 milesStandard Electronics40A, PG GC3Component WeightsBase 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. eachBattery Requirements⁴.6(2) 12 volt, U-1 batteriesBattery Charger3.5 amp, off-boardBattery HCPCSE2365Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month Battery: 13-month		
Overall Width³ 23.75" Overall Length³ 32.99"/44" (with footplate) Maximum Speed² Up to 4.3 mph Ground Clearance³ .75" at motor bracket Front Wheels 5" solid Drive Wheels 10" solid Rear Wheels 6" solid Drivetrain Two motor, mid-wheel drive® Regenerative and electromechanical Suspension Type Active-Trac® (ATS) High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range³,5 Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements⁴,6 (2) 12 volt, U-1 batteries Battery Charger Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Weight Capacity	300 lbs.
Overall Length ³ 32.99"/44" (with footplate) Maximum Speed ² Up to 4.3 mph Ground Clearance ³ .75" at motor bracket Front Wheels 5" solid Drive Wheels 10" solid Rear Wheels 6" solid Drivetrain Two motor, mid-wheel drive® Regenerative and electromechanical Suspension Type Active-Trac® (ATS) High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range ^{3,5} Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Turning Radius	22.5"
Maximum Speed ² Ground Clearance ³ Front Wheels Drive Wheels Drive Wheels Drivetrain Braking System Braking System Braking Suspension Type Active-Trac® (ATS) High-back Seat Sizes Drive Charge Range ^{3,5} Standard Electronics Battery Requirements ^{4,6} Battery HCPCS Up to 4.3 mph Two motor bracket B'' solid Regenerative and electromechanical Suspension Type Active-Trac® (ATS) High-back Seat Sizes Active-Trac® (ATS) High-back Seat Sizes Drive Trac® (ATS) Up to 19.4 miles Standard Electronics Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} Battery Charger Battery Charger Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Overall Width ³	23.75"
Ground Clearance ³ Front Wheels 5" solid Drive Wheels 10" solid Rear Wheels 6" solid Drivetrain Two motor, mid-wheel drive® Regenerative and electromechanical Suspension Type Active-Trac® (ATS) High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range ^{3,5} Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Overall Length ³	32.99"/44" (with footplate)
Front Wheels 5" solid Drive Wheels 10" solid Rear Wheels 6" solid Drivetrain Two motor, mid-wheel drive® Regenerative and electromechanical Suspension Type Active-Trac® (ATS) High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range³,5 Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Seat 50.2 lbs. Battery Requirements⁴,6 (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Maximum Speed ²	Up to 4.3 mph
Drive Wheels10" solidRear Wheels6" solidDrivetrainTwo motor, mid-wheel drive®Braking SystemRegenerative and electromechanicalSuspension TypeActive-Trac® (ATS)High-back Seat Sizes16" x 16"-18", 18" x 18"-20", 20" x 18"-20"Seat-to-Floor Range21"-22"Per Charge Range³.5Up to 19.4 milesStandard Electronics40A, PG GC3Component WeightsBase 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. eachBattery Requirements⁴.6(2) 12 volt, U-1 batteriesBattery Charger3.5 amp, off-boardBattery HCPCSE2365WarrantyFrame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Ground Clearance ³	.75" at motor bracket
Rear Wheels 6" solid Drivetrain Two motor, mid-wheel drive® Braking System Regenerative and electromechanical Suspension Type Active-Trac® (ATS) High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range³,5 Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements⁴,6 (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Front Wheels	5" solid
DrivetrainTwo motor, mid-wheel drive®Braking SystemRegenerative and electromechanicalSuspension TypeActive-Trac® (ATS)High-back Seat Sizes16" x 16"-18", 18" x 18"-20", 20" x 18"-20"Seat-to-Floor Range21"-22"Per Charge Range³,5Up to 19.4 milesStandard Electronics40A, PG GC3Component WeightsBase 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. eachBattery Requirements⁴,6(2) 12 volt, U-1 batteriesBattery Charger3.5 amp, off-boardBattery HCPCSE2365WarrantyFrame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Drive Wheels	10" solid
Braking System Regenerative and electromechanical Suspension Type Active-Trac® (ATS) High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range³,5 Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements⁴,6 (2) 12 volt, U-1 batteries Battery Charger Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Rear Wheels	6" solid
Suspension Type Active-Trac® (ATS) High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range ^{3,5} Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Drivetrain	Two motor, mid-wheel drive®
High-back Seat Sizes 16" x 16"-18", 18" x 18"-20", 20" x 18"-20" Seat-to-Floor Range 21"-22" Per Charge Range ^{3,5} Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Braking System	
Seat-to-Floor Range 21"-22" Per Charge Range ^{3,5} Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Batteries 25.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Warranty Electronics: 13-month Electronics: 13-month	Suspension Type	Active-Trac® (ATS)
Per Charge Range ^{3,5} Up to 19.4 miles Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	High-back Seat Sizes	
Standard Electronics 40A, PG GC3 Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Seat-to-Floor Range	21"-22"
Component Weights Base 94 lbs. (heaviest piece) Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Per Charge Range ^{3,5}	Up to 19.4 miles
Component Weights Seat 50.2 lbs. Batteries 25.2 lbs. each Battery Requirements ^{4,6} (2) 12 volt, U-1 batteries Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Standard Electronics	40A, PG GC3
Battery Charger 3.5 amp, off-board Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Component Weights	Seat 50.2 lbs.
Battery HCPCS E2365 Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Battery Requirements ^{4,6}	(2) 12 volt, U-1 batteries
Warranty Frame: 5-year limited Drivetrain: 13-month Electronics: 13-month	Battery Charger	3.5 amp, off-board
Warranty Drivetrain: 13-month Electronics: 13-month	Battery HCPCS	E2365
	Warranty	Drivetrain: 13-month Electronics: 13-month

- 1 Jazzy® Power Chairs are FDA Class II Medical Devices designed to aid individuals with mobility impairments.
- 2 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- 4 AGM or gel cell type required.
- 5 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 6 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of \pm or \pm 0. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.



(US) 800-800-8586 • (Canada) 888-570-1113 pridemobility.com

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

The information contained herein is correct at time of publication; we reserve the right to alter specifications without prior notice.

0004627-070522





Experience the simplicity and maneuverability of the Jazzy Select.[®] Equipped with Active-Trac[®] Suspension and dual motors, this power chair ensures a smooth, comfortable ride over uneven terrain. Mid-wheel drive offers a tight turning radius, making the Jazzy Select a perfect choice both indoors and out.

- Mid-wheel drive technology and a compact size is perfect for small spaces by offering a tight turning radius of 22.5"
- Dual in-line motors for enhanced efficiency, torque, range and performance
- Articulating rear caster beam works in conjunction with the ATX Suspension for a smooth ride over uneven surfaces
- Easy-access free-wheel lever
- Color-through shroud keeps the shroud looking new by reducing the visual scrapes and chips





Jazzy Red

Includes

Black vinyl, depthadjustable and limited recline standard comfort high-back with 60" lap belt:

- 16" W x 16"-18" D
- 18" W x 18"-20" D
- 20" W x 18"-20" D

Black vinyl high-back solid seat pan:

• Up to 20"W x 20"D

Options

- Elevating leg rests
- Heel loops
- Residual limb support
- Swing-away footrests
- Swing-away joystick

Accessories

- Cane/crutch holder
- Cup holder
- Flag
- Lap belt (50", 70", 80", 90")
- Oxygen holder
- Rear basket
- Safety flag
- Walker holder
- Weather cover—medium
 - -
- XLR USB
- Stealth Products[®] cushions: Zen, Essence and Glacial

Military Patches

