

ZOLAR

OUTSTANDING MANOEUVRABILITY,
OUTDOOR PERFORMANCE
AND LUXURY FEATURES

ZOLAR

The Pride® **Zolar** Scooter offers the manoeuvrability of a 3-wheel scooter along with high-performance features like full suspension and a hydraulic sealed brake system. The Zolar features sleek, aggressive style and a wealth of standard luxury touches including a wraparound delta tiller and LED lighting, making it the ultimate outdoor scooter.



Zolar
Shown above with optional pillow-top seat

Zolar

Model number:	SC613
Weight capacity:	181 kg
Maximum speed ¹ :	Up to 15 km/h
Ground clearance ² :	14.6 cm
Turning radius:	127.3 cm
Overall length ² :	139.7 cm
Overall width ² :	69.2 cm
Front tyres:	10 cm x 33 cm (pneumatic)
Rear tyres:	10 cm x 33 cm (pneumatic)
Suspension:	Front and Rear
Range per charge ^{1,4} :	Up to 37.16 km (with 92 AH batteries) Up to 30.01 km (with 70 AH batteries)
Maximum safe slope:	10°
Total weight without batteries:	108 kg
Heaviest piece when disassembled:	Main Frame: 82.8 kg
Standard seating:	Type: Captains Weight: 24.72 kg Material: Black Vinyl Dimensions: width – 45 cm depth – 45 cm
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Electronic, regenerative and electromechanical
Battery requirements ³ :	Two 12-volt, deep cycle Size: Group 27 (92 AH) or Group 24 (75 AH) Weight ⁵ : Group 27: 27.44 kg each; Group 24: 25 kg each
Battery charger:	8-amp, off-board

Colours:



Silver

Features

- Full suspension for optimal handling
- Large 33 cm pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and headlight
- Newly redesigned tiller with LCD console
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard

Options

- Double crutch holder
- Oxygen tank holder
- Rear basket
- Additional rearview mirror



New Tiller with LCD Console

¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or gel cell type required.

⁴Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.

⁵Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.