

MAXIMA

HEAVY-DUTY DESIGN & OUTSTANDING PERFORMANCE

MAXIMA


The Maxima Scooter combines heavy-duty design with elegance and outstanding performance. An impressive selection of enhanced standard features - 56 cm (22") wide medium-back seat, ultra-heavy duty drivetrain, rear suspension and an increased weight capacity of up to 35 Stone 10 lbs. (227 kg) - make the Maxima comfortable and give it enough brawn to tackle any challenge.



(Images are for illustration purposes only)

Maxima	3-wheel	4-wheel
Weight capacity:	35 Stone 10 lbs. (227 kg)	35 Stone 10 lbs. (227 kg)
Maximum speed ¹ :	Up to 4 mph (6 km/h)	Up to 4 mph (6 km/h)
Ground clearance ² :	8.1 cm (3.2")	8.1 cm (3.2")
Turning radius:	132.1 cm (52")	137.2 cm (54")
Overall length ² :	117.6 cm (46.3")	119.4 cm (47")
Overall width ² :	64.8 cm (25.5")	64.8 cm (25.5")
Front tyres:	7.5 cm x 25 cm (3" x 10") (solid)	7.5 cm x 25 cm (3" x 10") (solid)
Rear tyres:	10 cm x 25 cm (4" x 10") (solid)	10 cm x 25 cm (4" x 10") (solid)
Anti-tips:	Front and Rear	Rear
Suspension:	Rear	Rear
Total weight without batteries:	77.5 kg (171 lbs.)	80 kg (176 lbs.)
Heaviest piece when disassembled:	32 kg (70 lbs.) rear frame	32 kg (70 lbs.) rear frame
Standard seating:	Type: Deluxe contour, medium-back Weight: 19 kg (41 lbs.) Material: Grey Vinyl Dimensions: width – 56 cm (22") depth – 46 cm (18") height – 47 cm (18.5")	
Drive System:	Sealed transaxle, 24-volt DC motor	
Dual Braking System:	Regenerative and electromechanical	
Battery Requirements ³ :	Two 12-volt, deep cycle Size: 55 AH (standard) Weight ⁴ : 55 AH: 17 kg (38 lbs.)	
Battery Charger:	5-amp, off-board	

Colours:



Features

- 35 Stone 10 lbs. (227 kg) weight capacity
- Full directional light package
- Ultra heavy-duty drivetrain with 110-amp controller
- 64.8 cm (25.5") width for optimal stability
- Flat-free foam rubber-filled tyres
- Maximum speed up to 4 mph (6 km/h)
- Front basket standard
- Ergonomically enhanced 56 cm (22") wide x 47 cm (18.5") deep seating
- Durable and stylish rear polyurethane bumper
- User-friendly console
- Stylish micro-mag alloy wheels

Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Walker holder

¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of +10%, -5%.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or gel cell type required.

⁴Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.



32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
 (Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk