

# Pathrider® 143 XLD

OUTSTANDING MANOEUVRABILITY,  
OUTDOOR PERFORMANCE  
AND LUXURY FEATURES

## PATHRIDER® 143 XLD

The Pathrider® 143 XLD Scooter offers the manoeuvrability of a 3-wheel scooter along with high-performance features like full suspension and a hydraulic sealed brake system. The Pathrider 143 XLD features sleek, aggressive style and a wealth of standard luxury touches including a wraparound delta tiller and LED lighting, making it the ultimate outdoor scooter.



**Pride**<sup>®</sup>  
Mobility Products  
Australia Pty. Ltd.

— LIVE YOUR BEST —

(Tel) 03 8770 9600 • (Fax) 03 9703 2720 • [www.pridemobility.com.au](http://www.pridemobility.com.au)

# Pathrider® 143 XLD

Weight capacity:	181 kg (400 lbs.)
Maximum speed <sup>1</sup> :	Up to 16 km/h (10 mph)
Ground clearance <sup>2</sup> :	14.6 cm (5.75")
Turning radius <sup>2</sup> :	127.3 cm (50.12")
Overall length <sup>2</sup> :	139.7 cm (55")
Overall width <sup>2</sup> :	69.2 cm (27.25")
Front tyres:	10 cm x 33 cm (4" x 13") (pneumatic)
Rear tyres:	10 cm x 33 cm (4" x 13") (pneumatic)
Suspension:	Front and Rear
Range per charge <sup>1,4</sup> :	Up to 30.01 km (with 70 AH batteries)
Maximum allowable incline:	17.6% (10°)
Total weight without batteries <sup>2,6</sup> :	108 kg (238 lbs.)
Heaviest piece when disassembled <sup>2</sup> :	Main Frame: 82.8 kg (182.5 lbs.)
Standard seating:	Type: Captain Weight: 24.72 kg (54.5 lbs.) Material: Black Vinyl Dimensions: width – 45 cm (18"), depth – 45 cm (18") height – 47 cm (18.5")
Drive system:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Battery requirements <sup>3</sup> :	Two 12-volt, deep cycle Size: Group 24 (70 AH) Weight <sup>5</sup> : <b>70 AH</b> : 25 kg (55 lbs.) each
Battery charger:	8-amp, off-board

Colour:



## Features

- Full suspension for optimal handling
- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and headlight
- Newly redesigned tiller with LCD console
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rearview mirror standard

## Options

- Double crutch holder
- Oxygen tank holder
- Rear basket
- Additional rearview mirror



New Tiller with LCD Console

<sup>1</sup>Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of +10%, -5%.

<sup>2</sup>Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

<sup>3</sup>AGM or gel cell type required.

<sup>4</sup>Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.

<sup>5</sup>Battery weight may vary based on manufacturer.

<sup>6</sup>Includes standard seat.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.