

# Quantum® 6000

POWER CHAIR

Q6000 shown with TRU-Balance® Power Tilt & Recline and Q-Logic drive controls



## Limitless rehab capability.

The aggressively styled, Quantum® 6000 incorporates Mid-Wheel® 6 design and a powerful drivetrain for excellent overall performance and maximum torque. The Quantum 6000 is fully compatible with a broad range of seating and electronic options for limitless rehab capability.



# Specifications

<b>DRIVE WHEELS</b>	35.5 cm (14") pneumatic
<b>OMNI-CASTERS</b>	<b>Front:</b> 13 cm (5") solid <b>Rear:</b> 15 cm (6") solid
<b>SUSPENSION</b>	Active-Trac® ATX Suspension with integrated rear dual-strut suspension and articulating caster beam
<b>MAXIMUM SPEED</b>	Up to 10 km/h (6 mph) <sup>1</sup>
<b>BRAKES</b>	Intelligent Braking (electronic, regenerative disc brakes)
<b>GROUND CLEARANCE</b>	9 cm (3.5")
<b>TURNING RADIUS <sup>2</sup></b>	56 cm (22")
<b>OVERALL SIZE <sup>2</sup></b>	Length: 97 cm (38") Width: 65.7 cm (25.875")
<b>SEATING</b>	Synergy® Seat Adjustable Width: 25cm-61cm (10"-24") Adjustable Depth: 25cm-61cm (10"-24") TRU-Balance® Power Positioning System Adjustable Width: 35.5cm-61cm(14"-24") Adjustable Depth: 35.5cm-61cm(14"-24") High-back Seat 61cm X 61 cm (24" x 24")
<b>DRIVE TRAIN</b>	4-pole, Hammer Mid-Wheel 6®
<b>BATTERIES</b>	Two 12 volt, deep cycle Group 24
<b>RANGE PER CHARGE <sup>1</sup></b>	Up to 32 km (20 miles)
<b>BATTERY CHARGER</b>	8A, off-board
<b>AVAILABLE ELECTRONICS</b>	100A, Q-Logic (standard)
<b>WEIGHT CAPACITY</b>	136 kg (300 lbs.) maximum (user weight)
<b>BASE WEIGHT</b>	77 kg (170 lbs.)
<b>BATTERY WEIGHT <sup>3</sup></b>	24 kg (53.5 lbs.) (each)
<b>WARRANTY</b>	2-year limited warranty

# Colours



Metallic Red    Metallic Blue    Metallic Silver    Metallic Black    Sunburst Orange



# Features

- Mid-Wheel 6® allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance® Power Positioning
- OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Casters for enhanced performance over more varied terrain
- 4-pole Hammer motors
- Accepts (2) Group 24 & (1) NF-22 when used with a vent tray

# Options

- Solid tyres
- Swing-away joystick
- Multi-axis joystick mount
- Elevating leg rests
- Oxygen tank holder
- Neoprene leg rest sleeves
- Gel adductor buttons
- Vent tray
- TRU-Balance® power elevating seat
- TRU-Balance® lift & tilt
- Angle-adjustable footplates
- High-mount foot platform
- 70° drop-in footrests
- TRU-Comfort™ seating system
- Contoured seating with solid seat pan
- Q-Logic Drive Control System

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

### FOOTNOTES:

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure.
- 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3 %.
- 3) Battery weight may vary based on manufacturer.

