





# **Specifications**

DRIVE WHEELS	25.4 cm (10") pneumatic
OMNI-CASTERS	Front: 12.7 cm (5") solid
	<b>Rear:</b> 15.25 cm (6") solid
SUSPENSION	ATX Suspension
	(Active-Trac® with extra stability)
MAXIMUM SPEED 1	Up to 7.24 km/h (4.5 mph)
BRAKES	Intelligent braking
	(electronic, regenerative disc brakes)
GROUND CLEARANCE	6.35 cm (2.5")
TURNING RADIUS 2	54 cm (21.25") (without foot riggings)
OVERALL SIZE 2	Length: 88.25 cm (34.74")
	Width: 59 cm (23.23")
SEATING	Synergy® Seat
	Adjustable Width: 25 cm -51 cm (10"-20")
	Adjustable Depth: 25 cm -51 cm (10"-20")
	TRU-Balance® Power Positioning System
	Adjustable Width: 35.5 cm - 51 cm (14"-20")
	Adjustable Depth: 35.5 cm - 51 cm (14"-20") High-back Seat (51 cm x 51 cm (20" x 20") max. dim.)
	Medium-back Seat (51 cm x 51 cm (20" x 20") max. dim
DRIVETRAIN	2-motor, Mid-Wheel 6®
BATTERIES	Two 12 volt, deep cycle U-1
RANGE PER CHARGE <sup>1,3</sup>	Up to 18 km (11 miles)
BATTERY CHARGER	8A, off-board (std.)
AVAILABLE	
ELECTRONICS	Q-Logic
WEIGHT CAPACITY	136 kg (300 lbs.) maximum (user weight)
BASE WEIGHT	51 kg (112 lbs.)
BATTERY WEIGHT 4	11 kg (24.5 lbs.) (each)
WARRANTY	Lifetime limited warranty on frame;
	2-year warranty on electronics;
	18-month warranty on drive motor

### **Features**

- Mid-Wheel 6<sup>®</sup> allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance® Power Positioning
- OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Casters for enhanced performance over more varied terrain
- Easy front access to batteries
- Powerful GLIDE motors for added power and torque
- Off-board charger (5A PowerCube)

# <sup>n.)</sup> Options

- Swing-away joystick
- Multi-axis joystick mount
- Elevating leg rests
- Oxygen tank holder
- Neoprene leg rest sleevesGel adductor buttons
- Power elevating seat
- Angle-adjustable footplates
- 70° drop-in footrests
- On/off-board charger combo
- Solid tyres

## **Shroud Colours**



#### FOOTNOTES:

Tel: (03) 8770 9600

Fax: (03) 9703 2720

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure.
- 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.
- 3) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 4) Battery weight may vary based on manufacturer.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.





20-24 Apollo Drive Hallam, Victoria 3803 www.pridemobility.com.au

ACN 088 609 661 ABN 66 088 609 661

