

R-400

Rear-Wheel Drive Power Chair

R-400 shown with Euro 2 seating
and VR2 controller



The R-400 Rear-Wheel Drive Power Chair

The R-400 is designed for clients who demand manoeuvrability without sacrificing traditional rear-wheel drive performance.



Specifications

DRIVE WHEELS	35.5 cm (14") (only w/ 9" casters) standard
CASTERS	23 cm (9") solid
ANTI-TIPS	4" (10 cm)
MAXIMUM SPEED¹	Up to 8 km/h (5 mph)
BRAKES	Intelligent Braking (electronic, regenerative disc brakes)
GROUND CLEARANCE	7.6 cm (3")
OVERALL SIZE²	Length: 85 cm (33.5") without foot riggings Width: 64 cm (25")
SEATING	Euro 2
DRIVE TRAIN	2-motor, rear-wheel drive
BATTERY REQUIREMENTS	Two 12 volt, deep cycle
BATTERIE SIZE	50 AH (standard) 70 AH (optional)
RANGE PER CHARGE¹	Up to 32 km (21.75 miles)
BATTERY CHARGER	8A, off-board
AVAILABLE ELECTRONICS	60A PG VR2 controller (standard)
WEIGHT CAPACITY	136 kg (300 lbs.) maximum (user weight)
BATTERY WEIGHT	50 AH: 24 kg (53 lbs.) (each) 70 AH: 18 kg (40 lbs.) (each)
WARRANTY	2-year limited warranty

Colour



Metallic
Silver

"The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice".

"Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement".

Features

- Power tilt and power recline standard
- Outstanding tight-space manoeuvrability
- Narrow 64 cm (25") width and compact 85 cm (33.5") length
- Maximum speed of up to 8 km/h (5 mph)¹
- Adjustable seat frame
- Unique new design, seating system is integrated with the base
- Width and depth adjustable armrests

Options

- Flat-free tyres
- Pediatric legrests
- 70° swing-away footrests
- 80° heavy-duty leg rests
- 70° elevating leg rests
- Heel loops
- LED lighting

FOOTNOTES:

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tire pressure.
- 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3 %.