

RUGGED WITH FEATHER-TOUCH DISASSEMBLY



REVO® 2.0



Experience the **Revo® 2.0**, a rugged scooter that combines an array of features into one great package. Tough and built to last, the Revo 2.0 offers rugged dependability you expect from luxury mid-size scooters. Comfort-Trac Suspension (CTS) ensures a smooth and comfortable ride over varied terrain. Experience convenient, feather-touch disassembly for portability that is comparable to our Travel Mobility line. Enjoy standard under seat storage and speeds up to 8 km/h (5 mph). Ride on with the Revo 2.0!


PRIDE® **MOBILITY** SCOOTERS
LIVE YOUR BEST®

www.pridemobility.com.au





Specifications 3W: S66 4W: S67

| | |
|--|---|
| Weight Capacity | 170 kg (375 lbs.) |
| Maximum Speed | 8 km/h (5 mph) |
| Under Deck Clearance | 3W: 8.25 cm (3.25") at side deck 4W: 8.89 cm (3.5") at side deck |
| Ground Clearance | 3.2 cm (1.25") at transaxle |
| Turning Radius | 3W: 101.6 cm (40") 4W: 132.1 cm (52") |
| Overall Length | 3W: 116.9 cm (46") 4W: 119.4 cm (47") |
| Overall Width | 52.7 cm (20.75") |
| Seat-to-Ground Height | 59.7 cm (23.5") highest position; 53.3 cm (21") lowest position |
| Seat-to-Deck Height | 45.7 cm (18") |
| Front Tires | 3W: 3" x 8" (7.6 x 20.3 cm) 4W: 3" x 9" (7.6 x 22.9 cm) |
| Rear Tires | 3" x 9" (7.6 x 22.9 cm) |
| Suspension | Front and rear |
| Drive System | Two-motor, 24 volt DC motor |
| Dual Braking System | Regenerative and electro-mechanical |
| Range Per Charge ^{1,2} | 3W: Up to 19 km (12 miles) 4W: Up to 21 km (13 miles) |
| Total Weight Without Batteries ^{3,5} | 3W: 55 kg (120 lbs.) 4W: 60 kg (132 lbs.) |
| Heaviest Piece When Disassembled ³ | 3W: 21.8 kg (48 lbs.) (rear section) 4W: 25.9 kg (57 lbs.) (front section) |
| Standard Seating | Dimensions: Width: 50.8 cm (20") Depth: 45.7 cm (18") |
| Battery Requirements ⁴ | (2) U1 batteries; 11.5 kg (25 lbs.) each |
| Battery Charger | 3.5 amp |
| Color |   |

Grey Street True Blue

Features

- Comfort-Trac front and rear suspension
- Durable and stylish rear bumper
- Easily accessible tie down points (for transport of unoccupied scooter)
- Easily adjustable tiller
- Easily charge the batteries on or off the unit
- Pride's exclusive black, flat-free, non-scuffing tires
- Seat designed for extreme comfort
- Standard front basket
- Standard under seat storage
- Ultra heavy-duty drivetrain with 70 amp controller
- User-friendly console
- USB mobile device charging port

Accessories

- Pride® rear bag (includes crutch/walking stick holder)
- Walker holder (must have Pride® rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag
- Rearview mirror

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.

² Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

⁴ Battery weight may vary based on battery manufacturer.

⁵ Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



20-24 Apollo Drive Hallam, Victoria 3803
ACN 088 609 661 ABN 66 088 609 661

(Tel) 03 8770 9600 • (Fax) 03 9703 2720 • www.pridemobility.com.au

AU_REV02.0-SS-2-07-18



Pride®
Mobility Products
Australia Pty. Ltd.