## SOAR INTO ADVENTURE! Price



Digital Display



Rear LED Light Package



Front LED Light Package



Under Seat Storage

Soar into Adventure with the Pride® Raptor!

With speeds up to 14 mph and a 400 lb. weight capacity, it's the perfect scooter for anyone and everyone.

Travel greater distances with a per charge range up to 31 miles and experience a smoother ride over varied terrain with front and rear suspension.















## Specifications 3W: R3-1700

<u> </u>	
Weight Capacity	400 lbs.
Front Tires	3" x16"
Rear Tires	3" x16"
Maximum Speed <sup>1</sup>	Up to 14 mph
Ground Clearance <sup>3</sup>	3.5" at center of frame, 1.37" at anti-tip, 6.18" at highest point
Turning Radius <sup>3</sup>	60"
Overall Length <sup>3</sup>	59"
Overall Width³	24.75"
Seating	High back 20"W x 18"D (100° limited recline)
Seat-to-Ground Height	28"
Seat-to-Deck Height	19"
Total Weight Without Batteries	208 lbs.
Battery Weight	53 lbs.
Battery Requirements <sup>4,5</sup>	(2) 75 (Ah)
Range Per Charge <sup>1,2</sup> (Max.)	19 miles (up to 400 lbs. and full speed) 31 miles (up to 220 lbs. and at low speed)
Battery Charger	8 amp, off-board
Suspension	Front and rear
Heaviest Piece When Disassembled <sup>3</sup>	(Unit does not disassemble)
Warranty	2 year limited
Colors	

Silver

## **Features**

- Easy-to-read LCD console which shows estimated speed, mileage and battery display
- Front and rear suspension
- Front storage compartment located on the tiller
- Full LED lighting package with directional signals and brake lights that offer full visibility for increased safety
- Hand-brake with regenerative braking system
- Limited recline fold-flat seat with manual adjustment and angle/width adjustable armrests
- Secure, lockable under seat storage compartment with seat support rod
- Sleek and solid design for enhanced stability
- Tubeless pneumatic tires for a smooth ride
- Two rear-view mirrors

## Accessories

- Cup holder
- Saddle bag
- Safety flag
- XLR USB charger
- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections





