

Stability and Versatility in One Affordable Package



VICTORY® *Twin*



Dual front wheels
for added stability

The sleek, sporty **Victory**® **Twin** scooter delivers high-performance operation, all new features and feather-touch disassembly. With a full complement of advanced standard features like exclusive low-profile tires, dual front wheels for added stability and a wraparound delta tiller, the Victory® Twin is a greater value than ever before.



PRIDE®
MOBILITY
SCOOTERS

| pridemobility.ca |





Specifications SC712

Weight Capacity	350 lbs.
Maximum Speed ¹	Up to 5.25 mph
Ground Clearance ³	3" at mid-frame
Turning Radius ³	42"
Overall Length ³	46"
Overall Width ³	26"
Seat-to-Ground Height	23"-24.5"
Seat-to-Deck Height	17.5"-19"
Front Tires	Dual: 3" x 9" solid
Rear Tires	3.5" x 10" solid
Suspension	N/A
Range Per Charge ^{1,2}	Up to 11.1 miles
Total Weight Without Batteries ^{3,7}	150 lbs.
Heaviest Piece When Disassembled ³	55 lbs. (front section)
Standard Seating	Type: Foldable molded plastic Weight: 27.5 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth
Drive System	Rear-wheel drive sealed transaxle with 24-volt DC motor
Dual Braking System	Regenerative and electromechanical
Battery Requirements ^{3,4,5}	Size: (2) U-1 standard, Weight U-1: 24 lbs. each Size: (2) 40 AH (optional), Weight 40 AH: 32 lbs. each
Battery Charger	3-amp, off-board (U-1), 5-amp, off-board (40 AH)
Colors	 

Candy Apple Red Viper Blue

- ¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- ² Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- ³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- ⁴ AGM or gel cell type required.
- ⁵ Battery weight may vary based on battery manufacturer.
- ⁶ Includes standard seat weight.

Features

- Dual front wheels for added stability
- Feather-touch disassembly permits simple frame separation with only one hand for easy transport and storage
- Full lighting package, including high visibility automatic rear brake light system and turn signals
- Delta tiller provides ergonomic wraparound handles enables easy-to-use left or right hand operation and the ability to rest your wrist on the handle for added comfort
- Easy-to-read LED battery meter
- Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Long-lasting, maximum-intensity LED headlight offers optimal pathway illumination
- Lightweight pinchless hinge seat eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob
- Easy access, tiller-mounted charger port for standard dual voltage off-board charger
- 4-pole high-speed motors standard

Accessories

- Cane clip attachment
- Cane/crutch holder (*single, double*)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- 50", 60", 70" Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover
- XLR USB charger

Options

- 40 AH batteries with 5-amp, off board charger

Optional Seating

- Limited recline, black vinyl, high back with height adjustable headrest, flip-up height and width adjustable armrests
 - 18" x 18" (sliders) • 20" x 20" (no sliders) • 22" x 18" (no sliders)
- Deluxe contour high back black vinyl with height adjustable headrest, flip-up height and width adjustable armrests (no sliders)
 - 18" x 18" • 18" x 20" • 20" x 20" • 22" x 20"

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.