

End-to-End **Mobility Solutions**







	BAJA [®] WRANGLER [®] 2 Non-Medical Device*	BAJA [®] RAPTOR 2 Non-Medical Device*		BAJA[®] BANDIT FDA Class II Medical Device ¹
Model	BA400	BA300 (3-Wheel)	BA340 (4-Wheel)	BA140
Weight Capacity	450 lbs.	400 lbs.		400 lbs.
Maximum Speed ²	Up to 11.5 mph at 200 lbs. Up to 10.6 mph at 450 lbs.	Up to 13 mph at 400 lbs.	Up to 14 mph at 400 lbs.	Up to 8 mph at 400 lbs.
Ground Clearance ^{4,6}	8.25" at mid-frame 5.5″ at motor	3.58" at mid-frame		1.57" at motor skid plate 2.68" at front bumper 4.45" at mid-deck
Turning Radius ⁴	94.75″	59.64"	92.52"	53″
Overall Length/Overall Width ^{4,5}	61.25"/33"	59.3"/27.12"	62.2"/27.17"	49.6"/27.83"
Front Tires	14.5" Tubeless Pneumatic	16" Tubeless Pneumatic		9.4" Solid
Rear Tires	14.5" Tubeless Pneumatic	16" Tubeless Pneumatic		9.4" Solid
Range per Charge ^{2,9}	Up to 16.5 miles at 200 lbs. (75Ah) Up to 13.3 miles at 450 lbs. (75Ah)	Up to 31 miles at 220 lbs. (low-speed setting)	Up to 21.2 miles at 200 lbs. (low-speed setting)	Up to 14.5 miles at 200 lbs. (20Ah) Up to 11.25 miles at 400 lbs. (20Ah)
	Up to 21.4 miles at 200 lbs. (100Ah) Up to 17.3 miles at 450 lbs. (100Ah)	Up to 19 miles at 400 lbs. (high-speed setting)	Up to 15 miles at 400 lbs. (low-speed setting)	Up to 29 miles at 200 lbs. (40Ah) Up to 22.5 miles at 400 lbs. (40Ah)
Total Weight Without Batteries⁴	274 lbs.	212.8 lbs.	250.6 lbs.	162.6 lbs.
Standard Seating	Black vinyl, high-back with limited recline memory foam seat with sliders (16" X 16"-18" or 18" x 18"-20")	Black vinyl, high-back with limited recline memory foam seat with sliders (20" X 18")		Black vinyl, stadium seat with sliders (18" X 17")
Battery Requirements ⁷	(2) 75Ah ³ or (2) 100Ah ³	(2) 75Ah (included)		20Ah Lithium-ion or 40Ah Lithium-ion
Battery Weight [®]	48 lbs. each (75Ah) 60.5 lbs. each (100Ah)	52.5 lbs. each		20Ah: 20.8 lbs. 40Ah: 35.2 lbs.
Battery Charger	8a, off-board charger	8a, off-board charger		4a, off-board charger (Lithium-ion)
Seat to Floor Height	18.75"-20.25"	19.14″		18.11″
Seat to Ground Height	30″	28"		25.39″
Suspension	Front & Rear (CTS)	Front & Rear		Front & Rear
Standard Body Colors	Desert Sand, True Blue, Camo	Black (with color inserts ¹⁰), Candy Apple Red, True Blue		Sage, Tan, Camo
HCPCS	Non-Medical*	Non-Medical*		K0899**
Warranty	Lifetime limited on Frame 2-Year limited on Electronics 2-Year limited on Drivetrain 6-Month limited on Batteries	Lifetime limited on Frame 2-Year limited on Electronics 2-Year limited on Drivetrain 6-Month limited on Batteries		Lifetime limited on Frame 2-Year limited on Electronics 2-Year limited on Drivetrain 3-Year limited on Batteries

1. Pride FDA Class II Medical Devices are designed to aid individuals with mobility

mpairments. 2. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%.

Optional.
Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%.

5. Width of base (not including seat).

*Non-Medical Devices: This product is not a medical device and is not intended to assist, treat, diagnose, or alleviate any medical condition or illness. **K0899: Power Mobility Device, not coded by DME PDAC.

DME Providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement. HCPCS Codesprovided should not be considered as legal advice and do not guarantee reimbursement. Payer Coding, coverage, and bundling guidelines may apply.



800.800.8586

Does not account for anti-tip clearance.
Deep cycle (AGM or gel cell type recommended).
Battery weight may vary based on manufacturer.
Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
Inserts available in Candy Apple Red, True Blue, Evolution Orange, Green Machine, Lemon Crush, Pink Topaz and Matte Black.

The information contained herein is correct at the time of publication; we reserve the right to The information contained need in Source at the time of publication, we reserve the right after specifications without prior notice. Speed & range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %.

