FOOTNOTES

1. Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
2. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%.
3. Battery weight not included.
4. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%.
5. Battery pack is 19.5 lbs. with 12AH batteries.
6. Deep cycle (AGM or gel cell type recommended).
7. 18 AH battery pack weighs 29.5 lbs.
8. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
9. Battery weight may vary based on manufacturer.
10. Width of base (not including seat).
11. Includes standard seat weight.
12. Must be billed to Medicare as either a beneficiary requested upgrade with a properly executed ABN, or as an upgrade at no additional charge to the beneficiary..
13. Light package.
14. Interchangeable shrouds (all shroud panels included).
15. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

PRIDE® MOBILITY SCOOTERS

END-TO-END

	iRIDE® 2	i-Go™	Go Go® Endurance Li	Go Go® Ultra X	Go Go® ES 2	Go Go Elite Traveller®	Go Go Elite Traveller® 2	Go Go® Sport	Go Go® LX w/ CTS Suspension	Revo® 2.0
	Non-Medical Device*	Non-Medical Device*	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]
MODEL NUMBER	**S25**	**SC20**	**S54LXLIT**	**S39 (3-Wheel) S49 (4-Wheel)**	**S81**	**SC40E (3-Wheel) SC44E (4-Wheel)**	**SC442E**	**S73 (3-Wheel) S74 (4-Wheel)**	**S50LX**	**S66 (3-Wheel) S67 (4-Wheel)**
WEIGHT CAPACITY	250 lbs.	275 lbs.	325 lbs.	300 lbs.	250 lbs.	300 lbs.	300 lbs.	325 lbs.	300 lbs.	400 lbs.
SPEED (MAXIMUM)[2]	Up to 5.8 mph	Up to 4 mph	Up to 4.1 mph	3-Wheel: Up to 4.3 mph 4-Wheel: Up to 4.1 mph	Up to 4 mph	Up to 4 mph	Up to 4.2 mph	Up to 4.7 mph	Up to 6 mph	Up to 5.2 mph
GROUND CLEARANCE[4]	1.3" at motor	4.2" at mid-frame	1.5" at motor 3.25" at side deck	1.25" at motor 3.2" at mid-frame	0.75" at anti-tip 1.5" at motor	0.75" at anti-tip 2.25" at mid-frame	1.34"at transaxle	1.5" at motor 3" at mid-frame	0.75" at anti-tip 1.5" at motor 2.5" at frame	1.25" at motor
3-WHEEL TURNING RADIUS[4]	33.5"	45.9"	N/A	36.5"	31"	33"	N/A	36"	33.5"	40"
4-WHEEL TURNING RADIUS[4]	N/A	N/A	48.25"	52.25"	N/A	44"	37"	50.5"	N/A	52"
3-WHEEL LENGTH/WIDTH[4,10]	38"/19.25"	44"/20.3"	N/A	40.25"/19.25"	36.75"/19.5"	37"/19.5"	N/A	42"/21.25"	39.75"/20.5"	46"/20.75"
4-WHEEL LENGTH/WIDTH[4,10]	N/A	N/A	42"/20.5"	40.25"/19.25"	N/A	39.5"/19.5"	39.5"/19.5"	43"/21.25"	41.75"/20.5"	47"/20.75"
FRONT TIRES[4]	6.5" solid	8" hub motor	8" solid	8" solid	7.5" solid	3-Wheel: 8" solid 4-Wheel: 7" solid	7" solid	3-Wheel: 8" solid 4-Wheel: 9" solid	8" solid	3-Wheel: 8" solid 4-Wheel 9" solid
REAR TIRES[4]	6.75" solid	9" perforated	8" solid	8" solid	7.5" solid	8" solid	8" solid	9" solid	8" solid	9" solid
SUSPENSION	N/A	N/A	Front & Rear	N/A	N/A	N/A	N/A	N/A	Front & Rear	Front & Rear
RANGE PER CHARGE[2,8]	Up to 12 miles (200 lbs.) Up to 10 miles (250 lbs.)	Up to 9.3 miles (220 lbs.)[15] Up to 7 miles (275 lbs.)[15]	Up to 6.6 miles (200 lbs, 8 AH)[15] Up to 13.2 miles (200 lbs, 16 AH)[15]	3-Wheel: Up to 8 miles (200 lbs.) Up to 6.2 miles (300 lbs.) 4-Wheel: Up to 8.9 miles (200 lbs.) Up to 6.6 miles (300 lbs.)	Up to 6.24 miles (250 lbs.)	3-Wheel: Up to 7.3 miles (12Ah, 300 lbs.) Up to 10.5 miles (18Ah, 300 lbs.) 4-Wheel: Up to 6 miles (12Ah, 300 lbs.) Up to 9.75 miles (18Ah, 300 lbs.)	Up to 6.6 miles (12Ah, 300 lbs.) Up to 10.4 miles (18Ah, 300 lbs.)	3-Wheel: Up to 12.75 miles (325 lbs.) 4-Wheel: Up to 12 miles (325 lbs.)	Up to 6 miles (300 lbs.)	3-Wheel: Up to 17.4 miles (200 lbs.) Up to 12.8 miles (400 lbs.) 4-Wheel: Up to 17.8 miles (200 lbs.) Up to 14.8 miles (400 lbs.)
TOTAL WEIGHT WITHOUT BATTERIES[3,4,11]	42 lbs.	60.6 lbs.	93 lbs.	3-Wheel: 76.3 lbs. 4-Wheel: 81.5 lbs.	58 lbs.	3-Wheel: 75.5 lbs. 4-Wheel: 79.5 lbs.	83 lbs.	3-Wheel: 92.75 lbs. 4-Wheel: 100 lbs.	3-Wheel: 85 lbs. 4-Wheel: 90 lbs.	3-Wheel: 120 lbs. 4-Wheel: 132 lbs.
WEIGHT OF HEAVIEST PIECE[4]	32 lbs. (Scooter Base)	32.8 lbs. (Rear Base with Seat Back)	40.75 lbs. (Front Section)	3-Wheel: 29.5 lbs. (Front Section) 4-Wheel: 34.5 lbs. (Front Section)	41.4 lbs. (Scooter Base)	3-Wheel: 29.5 lbs. (Front Section) 4-Wheel: 34 lbs. (Front Section)	35 lbs. (Front Section)	3-Wheel: 35.75 lbs. (Front Section) 4-Wheel: 44 lbs. (Front Section)	33 lbs. (Front Section)	3-Wheel: 48 lbs. (Rear Section) 4-Wheel: 57 lbs. (Front Section)
STANDARD SEATING	Compact, Foldable (14.75" x 13.5")	Compact, Foldable with Removable Back (16" x 16")	Mesh Back (17" x 17")	Compact, Foldable (17" x 17")	Compact, Foldable (17" x 15")	Compact, Foldable (17" x 17")	Mesh Back (17" x 17")	Compact, Foldable (17" x 17")	Compact, Foldable (17" x 17")	Compact, Foldable (20" x 18")
BATTERY REQUIREMENTS	(1) 36V, 5.2Ah Lithium-ion	(1) 25.2V, 9.6Ah Lithium-ion	8Ah Lithium-ion pack or 16Ah Lithium-ion Pack	(2) 12Ah (SLA/AGM)	(2) 12Ah (SLA/AGM)	(2)12Ah (SLA/AGM) or (2)18Ah (SLA/AGM)	(2)12Ah (SLA/AGM) or (2)18Ah (SLA/AGM)	(2) 18Ah (SLA/AGM)	(2) 12Ah (SLA/AGM)	(2) U-1 (SLA/AGM)
BATTERY WEIGHT[9]	4.5 lbs.	4.8 lbs.	8 lbs. (8Ah)/ 12 lbs. (16Ah)	9 lbs. ea.[5]	9 lbs. ea.[5]	9 lbs. ea.[5] / 14 lbs. ea.[7]	9 lbs. ea.[5] / 14 lbs. ea.[7]	14 lbs. ea.[7]	9 lbs. ea.[5]	25 lbs. ea.
BATTERY CHARGER	Off-board, 36V (Lithium-ion)	Off-board, 3.5A (Lithium-ion)	Off-board, 3.5A (Lithium-ion)	Off-board, 2A	Off-board, 2A	Off-board, 2A	Off-board, 2A	Off-board, 2A	Off-board, 2A	Off-board, 3.5A
SEAT-TO-DECK HEIGHT RANGE	11.5" – 12.5"	14.6"	16.25"-17.75"	16.5"-18"	16.25"-17.25"	15.75"-17.25"	16.38"-17.83"	17"-18"	16.25"-17.75"	16.5" - 18"
SEAT-TO-GROUND HEIGHT RANGE[4]	19"- 20"	22.25"	21.25"-22.75"	21.5"-23"	20"-21"	18.25"-20.25"	21.38"-22.83"	20.5"-22"	20.75"-22.25"	22"-23.5"
STANDARD BASE COLORS	Mango Arctic Ice Blackberry Raspberry	Sugar Plum (matte) Iceberg Blue (matte) Black (matte) White (matte)	Garnet Red (Matte) Euro Grey [14]	Black	Black	Red Blue[14]	Cardinal Red, Black, Iceberg Blue, White Robin's Egg Blue, Chell-O, Sugar Plum, Tangerine	Red Blue[14]	Red Blue[14]	Grey Street True Blue
HCPCS CODE	Non-Medical*	Non-Medical*	K0899**	K0800 - Group 1 Standard	K0800 - Group 1 Standard (3-Wheel)	K0800 - Group 1 Standard	K0800 - Group 1 Standard	K0801 - Group 1 Heavy Duty	K0899**	K0899**
WARRANTY	3-year limited on frame 2-year limited on electronics 1-year limited on Drivetrain, Motor, Battery, and Charger	3-year limited on Frame 2-year limited on Electronics 1-year limited on Drivetrain, Motor, Battery, and Charger	Lifetime limited on Frame; 2-year limited on Electronics 2-year limited on Drivetrain 2-year limited on Battery	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime Limited on Frame; 2-year limited on Electronics; 2-year limited on Drivetrain 6-month limited on Batteries
	TRAVEL MOBILITY									

	Zero Turn 8	Zero Turn 10	Pursuit 2	PX4	Victory® 9	Victory® 10	Victory® 10.2	Victory® LX Sport[13]	Maxima[13]
	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]	FDA Class II Medical Device[1]
MODEL NUMBER	**JAZZYZTS**	**S710ZT**	**SC7132**	**SC134**	**SC609 (3-Wheel) SC709 (4-Wheel)**	**S610 (3-Wheel) S710 (4-Wheel)**	**S6102**	**S710LXW**	**SC901 (3-Wheel) SC941 (4-Wheel)**
WEIGHT CAPACITY	325 lbs.	400 lbs.	400 lbs.	500 lbs	300 lbs.	400 lbs.	400 lbs.	400 lbs.	500 lbs.
SPEED (MAXIMUM)[2]	Up to 5.9 mph	Up to 7.3 mph	Up to 9.3 mph	Up to 9.2 mph	Up to 5.3 mph	Up to 5.3 mph	Up to 5.2 mph	Up to 8 mph	Up to 5.8 mph
GROUND CLEARANCE[4]	1.3" at motor 1.5" at anti-tip 3.5" at side deck	2" at motor 3" at mid frame	3.78" at transaxle 4.6" at mid-frame	3.5" at motor 4.4" at mid-frame	3-Wheel: 1.4" at anti-tip 1.8" at transaxle 2" at mid-frame 4-Wheel: 1.25" at anti-tip 1.75" at motor 2.5" at mid-frame	3-Wheel: 1.26" at anti-tip 2.2" at motor 3" at mid-frame 4-Wheel: 2" at motor 1.5" at anti-tip 3" at mid-frame	2.4" at transaxle 2.1" at anti-tip 3" at side deck	2.2" at motor 3.15" at rear mid-frame	3-Wheel: 2.5" at motor 3" at mid-frame 4-Wheel: 2.25" at motor
3-WHEEL TURNING RADIUS[4]	N/A	N/A	N/A	N/A	40.25"	42"	42"	N/A	49"
4-WHEEL TURNING RADIUS[4]	37.25"	43"	69.3"	82.3"	51.5"	54"	N/A	61.3"	53"
3-WHEEL LENGTH/WIDTH[4,10]	N/A	N/A	N/A	N/A	43.5"/22.25"	45.25"/22.25"	45"/22.25"	N/A	47.5"/27"
4-WHEEL LENGTH/WIDTH[4,10]	45.75"/20.75"	48"/24.25"	57.5"/29.7"	56"/27"- 27.8"	45.5"/22.5"	47"/22.25"	N/A	47"/25.5"	47.5"/27"
FRONT TIRES[4]	7" solid	9" solid	13" pneumatic	13" pneumatic	3-Wheel: 8" solid 4-Wheel: 9" solid	10" solid	10" solid	10" solid	3-Wheel: 10.5" solid 4-Wheel: 10" solid
REAR TIRES[4]	9" solid	10.75" solid	13" pneumatic	13" pneumatic	9" solid	10" solid	10" solid	10" solid	10.75" solid
SUSPENSION	Front & Rear	Front & Rear	Front & Rear	Front & Rear	N/A	N/A	N/A	Front & Rear	N/A
RANGE PER CHARGE[2,8]	Up to 13.1 miles (200 lbs.) UP to 11 miles (325 lbs.)	Up to 21.2 miles (200 lbs.) Up to 15.9 miles (400 lbs.)	Single Battery: Up to 17.4 miles (220 lbs.) Up to 13.8 miles (400 lbs.) Dual Battery: Up to 34.8 miles (220 lbs.) Up to 30.9 miles (350 lbs.)	Up to 23.4 miles (220 lbs.) Up to 14 miles at (500 lbs.)	3-Wheel: Up to 18 miles (300 lbs.) 4-Wheel: Up to 16.3 miles (300 lbs.)	Up to 15.5 miles (400 lbs.)	Up to 13 miles (40Ah, 400 lbs.) Up to 11 miles (U-1, 400 lbs.)	Up to 19.7 miles (200 lbs.) UP to 13 miles (400 lbs.)	3-Wheel: Up to 19.8 miles (500 lbs.) 4-Wheel: Up to 19.5 miles (500 lbs.)
TOTAL WEIGHT WITHOUT BATTERIES[3,4,11]	120 lbs.	181.8 lbs.	220.6 lbs.	253.8 lbs.	3-Wheel: 117 lbs. 4-Wheel: 131 lbs.	3-Wheel: 133 lbs. 4-Wheel: 137 lbs.	130.25 lbs.	160 lbs.	3-Wheel: 183.5 lbs. 4-Wheel: 196.5 lbs.
WEIGHT OF HEAVIEST PIECE[4]	48 lbs. (Rear Section)	75 lbs. (Front Section)	163 lbs. (Base)	201.2 lbs. (Base)	3-Wheel: 48.5 lbs. (Front Section) 4-Wheel: 59 lbs. (Front Section)	3-Wheel: 54 lbs. (Front Section) 4-Wheel: 63 lbs. (Front Section)	56.5 lbs. (Front Section)	77 lbs. (Front Section)	N/A (unit does not disassemble)
STANDARD SEATING	Compact, Foldable (17" x 17")	Compact, Foldable (18" x 17")	Limited Recline High Back, with Sliders (18" X 18")	Limited Recline High Back (18"x18")	Compact, Foldable (18" x 17")	Compact, Foldable (18" x 17")	Foldable (18"x17")	Limited Recline High Back with Sliders & Headrest (18" x 18")	Depth-Adjustable Limited Recline High Back (22"x 18"–20")
BATTERY REQUIREMENTS	(2) 22Ah (SLA/AGM)	(2) 40Ah (SLA/AGM)	(1) or (2) 24V, 50Ah Lithium-ion	(2) 12V 75Ah (SLA/AGM)	(2) U-1 (SLA/AGM)	(2) U-1 (SLA/AGM) or (2) 40AH (SLA/AGM)	(2) U-1 (SLA/AGM) or (2) 40Ah (SLA/AGM)	(2) 50Ah (SLA/AGM)	(2) GEL, 58Ah, NF-22 (Nano-silica)
BATTERY WEIGHT[9]	32 lbs. (Battery box)	30.25 lbs. ea	23.8 lbs. ea.	48.8 lbs. ea.	24 lbs. ea	24 lbs. ea./ 32 lbs. ea.	24 lbs. ea./ 32 lbs. ea.	30.2 lbs. ea.	36.5 lbs. ea.
BATTERY CHARGER	Off-board, 3.5A	Off-board, 3.5A	Off-board, 8A	Off-board, 8A	Off-board, 3.5A	Off-board, 3.5A (U-1)/ Off-board, 5A (40Ah)	Off-board, 3.5A (U-1)/ Off-board, 5A (40Ah)	Off-board, 5A	Off-board, 5A
SEAT-TO-DECK HEIGHT RANGE	17"-18.5"	17.75"-19.25"	17.9"-20.9"	16.54"-18.39"	17.25"-18.75"	17.5"-19"	17.5" – 18"	16.5"-18.5"	17.13" - 19.13"; 17.36"-23.61" (with power elevating seat)
SEAT-TO-GROUND HEIGHT RANGE[4]	22"-23.5"	23.25"-24.75"	28.74"	24.17"-25.59"	22.5"-24"	23.5"-25"	23.5"- 25"	23"- 25"	22.1" - 24.1" 22.32"-28.57" (with power elevating seat)
STANDARD BASE COLORS	Green Moonstone Onyx Black Pearl White Sapphire Blue Fire Opal, Pewter	Candy Apple Red Ocean Blue (matte) Pearl White Black (matte)	Black Grey (matte) Orange	Satin Aluminum Dark Violet, Red Peacock Blue, Sunflower, Camo	Candy Apple Red	Candy Apple Red Viper Blue	Candy Apple Red Ocean Blue (matte)	Candy Apple Red True Blue	Garnet Red (matte) Ocean Blue (matte)
HCPCS CODE	K0899**	K0899**	K0899**	K0899**	K0800 - Group 1 standard	K0801 - Group 1 Heavy Duty	K0801 - Group 1 Heavy Duty	K0899**	K0802- Group 1 Very Heavy Duty (3-Wheel) K0808- Group 2 Very Heavy Duty (4-Wheel)[12]
WARRANTY	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime Limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 3-year limited on Battery	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Battery	Lifetime Limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteriess	Lifetime limited on Frame 2-year limited on Electronics 2-year limited on Drivetrain 6-month limited on Batteries
	ZERO-TURN SERIES	**MID-SIZE LUXURY**							**HEAVY-DUTY**

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed & range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3 %.

DME providers are responsible for determining the appropriate billing codes when submitting for insurance reimbursement. HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. Payer coding, coverage, and bundling guidelines may apply.

*Non-Medical Devices: This product is not a medical device and is not intended to assist, treat, diagnose, or alleviate any medical condition or disability.
**K0899: Power mobility device, not coded by DME PDAC.

pridemobility.com

Rev C/June 2024

INFINFB4551