SELECT 6

The Jazzy Select<sup>®</sup> 6 provides maximum front stability, combined with the advantages of in-line motor technology. Active-Trac<sup>®</sup> Suspension and 6" front and rear castors offer superior performance indoors and out. An impressive selection of standard convenience features make it the easiest power chair to use.



SPECIFICATIONS	;
Weight capacity	21 Stone 6 lbs. (136 kg)
Maximum speed <sup>1</sup>	Up to 4 mph (6.44 km/h)
Ground clearance	5.08 cm (2.0")
Turning radius <sup>2</sup>	55.56 cm (21.8750")
Overall length <sup>2</sup>	89.85 cm (35.3750")4
Overall width <sup>2</sup>	59.69 cm (23.5")
Wheels	Drive: 25.4 cm (10") solid
Anti-tips	N/A
Castors	15.24 cm (6") solid (front and rear)
Suspension	Active-Trac <sup>®</sup>
Drivetrain	Two-motor, in-line, mid-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	40 amp, PG GC/ 60 amp VR2 (with power elevating seat)
Specialty controls	No
Battery charger	Off-board, 5 amp (standard)
Battery requirements	(2) 12 volt deep cycle
Battery size	(U-1) 30 AH
Battery weight <sup>3</sup> Base weight Standard seat weight	11.11 kg (24.5 lbs.) each 45.36 kg (100 lbs.) 16.78 kg (37 lbs.) high back
Max. seat dimensions	46 cm x 46 cm (18" x 18")
Warranty	Lifetime warranty on frame; 1-year limited warranty on electronics; 18-month warranty on PG Drive control system; 2-year limited warranty on drivetrain

## FEATURES

- 15.24 cm (6") castors on front and rear for maximum stability
- In-line motor technology for increased efficiency, torque and range
- 40 amp, PG GC contoller/ 60 amp VR2 (some models)
- Articulating rear castor beam
- Battery removal through side panel
- Easy access charger port and circuit breaker
- Service friendly access to controller
- Height and depth-adjustable foot platform

## OPTIONS Power elevating seat Cup holder Rear basket

- Oxygen tank holder
- Cane/crutch holder
- Walker holder

**COLOURS** 

Red

Blue

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

- 1) Speed varies with user weight, terrain type, battery charge, battery condition and tyre pressure.
- Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.
- 3) Battery weight may vary based on manufacturer.
- Without foot riggings.



32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL (Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk