

PRODUCT SPECIFICATIONS SHEET

Model: Jet 3 Ultra

Manufacturer: Pride Mobility Products Australia Pty. Ltd.

Internet Address: www.pridemobility.com

Document Information: INFINF2766/Rev A/December 2011

Suspension:	Active Trac
Drive Wheels:	25 cm (10 in.), pneumatic or solid available
Caster Wheels:	20.32 cm (8 in.) solid
Anti-tip Wheels:	12.7 cm (5 in.) solid
Maximum Speed: ¹	Up to 6 km/h (4 mph)
Range: ^{1, 4}	Up to 15 km (9.32 miles)
Brakes:	"Intelligent Braking" electronic regenerative, disc park brake
Ground Clearance: ²	8.6 cm (3.25 in.) at center of base
Turning Radius: ²	55.88 cm (22 in.) with front riggings
Overall Size: ^{2, 6}	Length: 103.5 cm (40.75 in.) with front riggings 91.44 cm (36 in.) without front riggings Width: 60.96 cm (24 in.)
Drivetrain:	Two motor, mid-wheel drive
Batteries: ³	Two 12-volt, deep-cycle batteries
Battery Charger:	3.5 amp, off-board
Weight Capacity:	136 kg (300 lbs.)
Component Weights: ⁵	Base: 43.8 kg (96.5 lbs.) Batteries: 9.53 kg (21 lbs.) each
Class of Use:	A
Maximum Allowable Incline:	10.5% (6°)
Maximum Angle Capacity:	17.6% (10°)
Maximum Obstacle Climbing Ability:	6.55 cm (2.58 in.)

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tyre type, and tyre condition. This specification is subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See VI. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 Series EN12184 standards. All specifications subject to change without notice.

* I N F I N F B 2 7 6 6 *

