

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy Select Elite

Manufacturer: Pride Mobility Products Australia Pty. Ltd.

Internet Address: www.pridemobility.com

Document Information: INFINF2787/Rev A/November 2011

Class of use:	Class A
Suspension:	Limited
Drive Wheels:	22.86 cm (9 in.), solid
Caster Wheels:	15.24 cm (6 in.), solid, rear-mounted
Anti-tip Wheels:	7.62 cm (3 in.) solid, front-mounted
Maximum Speed: ¹	Up to 6.44 km/h (4 mph)
Range: ^{1, 4}	Up to 21.97 km (13.65 miles)
Brakes:	"Intelligent Braking" electronic regenerative, disc park brake
Ground Clearance: ²	3.81 cm (1.5 in.) at anti-tips 6.35 cm (2.5 in.) at battery box 3.81 cm (1.5 in.) at motors
Maximum Allowable Incline:	10.5% (6°)
Maximum Angle Capacity:	17.6% (10°)
Maximum Obstacle Climbing Ability:	4 cm (1.57 in.)
Turning Radius: ²	61 cm (24 in.)
Overall Size: ^{2, 6}	Length: 87.3 cm (34.375 in.) without front riggings 102.9 cm (40.5 in.) with front riggings Width: 58.4 cm (23 in.)
Drivetrain:	Two motor, front-wheel drive
Batteries: ³	Two 12-volt, U-1 batteries
Battery Charger:	3-amp, off-board
Weight Capacity:	136 kg (300 lbs.)
Component Weights: ⁵	Base: 51 kg (112.5 lbs.) Standard Seat (Comfort Seat): 17.7 kg (39 lbs.) Batteries: 11.11 kg (24.5 lbs.) each

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tyre type, and tyre condition. This specification can be subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See VI. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA WC Vol 2, Section 4 and ISO 7176-4 Standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI-RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.

