

PRODUCT SPECIFICATIONS

Model: Victory XL140 (SC714)

Manufacturer: Pride Mobility Products Europe B.V.

Internet Address: www.pridemobility.com

Document Information: INFINF2676/Rev A/June 2011

Model Number	SC714
Class	C
Maximum Allowable Incline ⁷	17,6% (10°)
Maximum Angle Capacity	17,6% (10°)
Obstacle Climbing Ability	13 cm (5 in.)
Overall Length ²	142,8 cm (56,25 in.)
Overall Width ²	69,2 cm (27,25 in.)
Total Weight Without Batteries ^{2, 5}	117,70 kg (259,5 lbs.)
Heaviest Piece When Disassembled	Main frame: 93,21 kg (205,5 lbs.)
Turning Radius ²	Right: 210,8 cm (83 in.); Left: 208,3 cm (82 in.)
Speed (Maximum) ¹	Standard: 15 km/h (9,42 mph); Optional: 10 km/h (6,21 mph)
Range Per Charge ^{1, 4}	100 Ah batteries: Standard - Up to 46,57 km (28,94 miles) Optional - Up to 42,18 km (26,2 miles)
Ground Clearance ²	13,33 cm (5,25 in.)
Weight Capacity	181 kg (400 lbs.)
Standard Seating	Type: Captain Weight: 21,77 kg (48 lbs.) Material: Black Vinyl Dimensions: 49,53 cm (19,5 in.) overall width 44,45 cm (17,5 in.) effective depth 47 cm (18,5 in.) height
Drive System	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System	Regenerative and electromechanical
Tires	Type: Pneumatic Front and rear: 33 cm (12,9 in.)
Battery Requirements ^{3, 6}	Two 12-volt, deep-cycle Size: Group 31 (100 Ah) Battery weight: 27,44 kg (60,5 lbs.) each
Battery Charger	8-amp, off-board
Freewheel Operational Force	69 Newtons (50,89 foot-pound force)

¹ Varies with user weight, terrain type, battery amp-hour (Ah), battery charge, battery condition and tire condition. This specification can be subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See IV. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity with Group 31.

⁵ Includes standard seat.

⁶ Battery weight may vary based on manufacturer.

⁷ Tested in accordance with ISO7176-22, 2000 and ISO 7176-11, 1992 standards.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.

* I N F I N F B 2 6 7 6 *

