

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy Elite ES-1

Manufacturer: Pride Mobility Products Corp.

Internet Address: www.pridemobility.com

Document Information: INFINF3204/Rev A/June 2013

Class of Use:	A
Weight Capacity:	300 lbs. (136 kg)
Maximum Speed: ¹	Up to 4 mph (6.44 km/h)
Ground Clearance: ²	2.5 in. (6.35 cm) at battery tray 0.75 in. (1.9 cm) at motors
Turning Radius: ²	23.5 in (59.7 cm)
Overall Size: ^{2, 6}	Length: 39 in. (99 cm) with front riggings 34.75 in. (88.27 cm) without front riggings Width: 22.75 in. (57.79 cm)
Drive Wheels:	9 in. (22.86 cm), solid
Caster Wheels:	6 in. (15.24 cm), solid, rear-mounted
Anti-tip Wheels:	5 in. (12.7 cm), solid, front-mounted
Suspension:	Limited
Range: ^{1, 4}	Up to 12 miles (19.3 km)
Component Weights: ⁵	Base: 68.5 lbs. (31.07 kg) Standard Seat (Comfort Seat): 43 lbs. (19.5 kg) Batteries: 18 lbs. (8.2 kg) each
Drivetrain:	Two motor, front-wheel drive
Brakes:	"Intelligent Braking" electronic regenerative, disc park brake
Batteries: ³	Two 12-volt, U-1 batteries
Battery Charger:	3-amp, off-board
Maximum Allowable Incline:	6° (10.5%)
Maximum Angle Capacity:	10° (17.6%)
Maximum Obstacle Climbing Ability:	1.6 in. (4 cm)

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification can be subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See VI. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA WC Vol 2, Section 4 and ISO 7176-4 Standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI-RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.

